

imageRUNNER ADVANCE DX C568iF Series

Color
Compact
Multifunction

Print up to 60 ppm (BW/color)

Scan up to 200 ipm (300 dpi) (BW/color, duplex)

Print up to 8-1/2" × 14"

2,300-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE DX multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touch screen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive.¹
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.
- Hot Folders allow users to drag and drop a file into a hot folder and automatically print with predefined settings such as number of copies and finishing requirements.



SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM*² systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control³ utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.⁴



QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V² color profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished plus intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.

* Security Information and Event Management



DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold.⁵

CONFIGURATION OPTIONS

imageRUNNER ADVANCE DX C568iF Series

imageRUNNER ADVANCE DX
C568iF/C478iF



imageRUNNER ADVANCE DX
C568iFZ/C478iFZ



CASSETTE FEEDING UNIT-AS1

- 550-sheet capacity and cabinet for storage
- Supports up to Legal
- Supports 16 lb. Bond to 60 lb. Cover



CASSETTE FEEDING UNIT-AT1

- 1,650-sheet capacity
- Supports up to Legal
- Supports 16 lb. Bond to 60 lb. Cover



CASSETTE MODULE-AJ1**

- Desktop configuration
- 550-sheet capacity
- Supports up to Legal
- Supports 16 lb. Bond to 60 lb. Cover

* Finisher cannot be added after purchase.

** Up to two optional cassettes can be added to the iF model.
One optional cassette can be added to the iFZ model.
Applies to floor standing and desktop configurations.

Main Unit

Type

Color Laser Multifunctional

Core Functions

Print, Copy, Scan, Send, Store, Fax

Processor

1.75 GHz Dual Core Processor

Control Panel

10.1" TFT LCD WSVGA Color Touch-panel

Memory

4.0 GB RAM

Solid State Drive

256 GB

Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,
Wireless LAN (IEEE 802.11 b/g/n)

Optional: Bluetooth Low Energy
Others

Standard: USB 2.0 (Host) x2, USB 3.0 x1 (Host),
USB 2.0 x1 (Device)

Optional: Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 650 Sheets

Maximum: 2,300 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: 550-sheet Paper Cassette,
100-sheet Multi-Purpose Tray

Optional: 1,650-sheet Paper Cassette
(Cassette Feeding Unit-AT1)
550-sheet Paper Cassette
(Cassette Feeding Unit-AS-1)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard

Model: 400 Sheets

Finisher 900 Sheets (400 sheets: base tray, 400

Model: sheets: upper tray, 100 sheets: lower tray)

Finishing Capabilities

Standard: Collate, Group

Finisher: Collate, Group, Offset, Staple

Supported Media Types

Multi-Purpose Thin, Plain, Recycled, Heavy, Color,

Tray: Bond, Envelope, Letterhead

Cassette: Thin, Plain, Recycled, Heavy, Color,
Label, Bond, Letterhead

Supported Media Sizes

Multi-Purpose Legal, Letter, Executive, Statement,
Tray: Envelopes [No.10 (COM10), Monarch, DL,
ISO-C5], Custom size: 3" x 5" to 8-1/2" x 14"
(76.2 x 127.0 mm to 216.0 x 355.6 mm)

Cassette: Legal, Letter, Executive, Statement,
Custom Size: 4" x 5-7/8" to 8-1/2" x 14"
(101.6 x 148.0 mm to 216.0 x 355.6 mm)

Supported Media Weights

Cassettes: 16 lb. Bond to 60 lb. Cover (60 to 163 g/m²)

Multi-Purpose

Tray: 16 lb. Bond to 79 lb. Cover (60 to 216 g/m²)

Duplex: 16 lb. Bond to 60 lb. Cover (60 to 163 g/m²)

Print/Copy Speed (BW and Color)

C568iF/

C568iFZ: Up to 60 ppm (Letter), Up to 47 ppm (Legal)

C478iF/

C478iFZ: Up to 50 ppm (Letter), Up to 39 ppm (Legal)

Warm-up Time

From Power

On: Approx. 10 Seconds⁶

From Sleep

Mode: Approx. 10 Seconds⁷

Quick Startup

Mode: Approx. 4 Seconds⁸

Dimensions (W x D x H)

Standard 20-1/2" x 25-1/4" x 26-3/8"

Model: (521 mm x 642 mm x 668 mm)

Finisher 20-1/2" x 25-1/4" x 34"

Model: (521 mm x 642 mm x 864 mm)

Installation Space (W x D)

37-3/8" x 33-1/8" (950 mm x 840 mm) (with Left Cartridge
Door Open + Right Door Open + the Cassette Drawer Open)

Weight⁹

Standard

Model: Approx. 101.4 lb. (46 kg)

Finisher Model: Approx. 121.3 lb. (55 kg)

Print Specifications

Print Resolution (dpi)

Up to 1200 x 1200 (equivalent)

Standard Page Description Languages

UFR II, PCL6, Adobe® PostScript® 3™

Direct Print

Available from USB, Advanced Box,
Remote UI, and Web Access

Supported File Types

PDF, TIFF, JPEG, EPS, XPS

Printing from Mobile Devices and Cloud-based Services

A range of standard and optional software and MEAP-
based solutions (including AirPrint, Mopria, Universal
Print by Microsoft®, Canon PRINT Business, and uniFLOW
Online) are available to provide printing from mobile
devices or Internet-connected devices and cloud-based
services depending on your requirements. Please contact
your sales representative for further information.

Fonts

PCL: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T (Japanese,
Korean, Simplified and Traditional
Chinese),¹⁰ Barcode Fonts¹¹

PS: 136 Roman

Operating System¹²

UFR/II/PS: Windows® 8.1/10/Server 2012/Server 2012
R2/Server 2016/Server 2019,
Mac OS X(10.11 or later)

PCL: Windows 8.1/10/Server 2012/Server 2012
R2/Server 2016/Server 2019

PPD: Windows 8.1/10, Mac OS X(10.10 or later)

Copy Specifications

First-Copy-Out Time (LTR)

C568iF/
C568iFZ: Approx. 4.4/5.2 seconds or less

C478iF/
C478iFZ: Approx. 5.1/5.8 seconds or less

Copy Resolution (dpi)

600 x 600

Multiple Copies

Up to 9,999

Magnification

25 to 400% (1% Increments)

Preset Reductions/Enlargements

25%, 50%, 64%, 78%, 100% (1:1), 129%, 200%, 400%

Scan Specifications

Type

Single-Pass Duplexing Automatic Document Feeder¹³

Document Feeder Paper Capacity

Up to 100 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

Legal, Letter, Statement, Custom Size: 1-7/8" x 5"
to 8-1/2" x 14" (48.0 mm x 128.0 mm to 216.0 mm x
355.6 mm), Business Card: 1-7/8" x 3-3/8" to 2-1/8" x
3-5/8" (48.0 mm x 85.0 mm to 55.0 mm x 91.0 mm)

Document Feeder Supported Media Weights

Single-Sided 13.3 to 34 lb. Bond (50 to 128 gsm) (BW);

Scanning: 17 to 34 lb. Bond (64 to 128 gsm) (CL)

Double-Sided 13.3 to 34 lb. Bond (50 to 128 gsm) (BW);

Scanning: 17 to 34 lb. Bond (64 to 128 gsm) (CL)

Business Card: 21.3 lb. Bond to 80 lb. Cover (80 to 220 gsm)

Platen Acceptable Originals

Sheet, Book

Pull Scan

Color Network ScanGear2 for both Twain and WIA

Supported Windows 8.1/10/Server 2012/Server 2012

OS: R2/Server 2016

Scan Resolution (dpi)

Scan for Copy: 600 x 600

Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/
IFAX), (Pull) 600 x 600

Scan for Fax: 600 x 600

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to
compatible mobile devices and certain cloud-based
services depending on your requirements.

Scan Speed (LTR)

Send: Automatic Color Select "OFF" (300 x 300 dpi):

Single-Sided Scanning: 100 ipm

Double-Sided Scanning: 200 ipm

Automatic Color Select "ON" (300 x 300 dpi):

Single-Sided Scanning: 50 ipm

Double-Sided Scanning: 100 ipm

Copy: Scan Speed Priority (300 x 600 dpi):

Single-Sided Scanning: 50 ipm

Double-Sided Scanning: 100 ipm

Image Quality Priority (600 x 600 dpi):

Single-Sided Scanning: 30 ipm

Double-Sided Scanning: 50 ipm

Send Specifications

Destination

Standard: Email/Internet Fax (SMTP), SMB v3.0,
FTP, WebDAV, Mail Box, Super G3 Fax

Optional: IP Fax

Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

Push: Up to 600 x 600

Pull: Up to 600 x 600

Communication Protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV

Email: SMTP, POP3

File Format

TIFF, JPEG, PDF (Compact, Searchable, Apply policy,
Optimize for Web, PDF A/1-b, Trace & Smooth, Encrypted,
Device Signature, User Signature), XPS (Compact,
Searchable, Device Signature, User Signature), Office
Open XML (PowerPoint, Word)

Fax Specifications

Maximum Number of Connection Lines

1

Modem Speed

Super G3: 33.6 Kbps

G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400 (Ultra Fine), 200 x 400 (Super Fine),

200 x 200 (Fine), 200 x 100 (Normal)

Sending and Recording Size

Statement to Legal

Fax Memory

Up to 30,000 Pages (2,000 jobs)

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast

Max. 256 Addresses

Memory Backup

Yes

Store Specifications

Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, Maximum 10,000 Pages (2,000 jobs) Stored

Advanced Box

Communication

Protocol: SMB or WebDAV Supported

Client PC: Windows 8.1/10

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB

Security Specifications

Authentication

Standard: Universal Login Manager (Device and Function Level Log-in), uniFLOW Online Express,¹⁴ User Authentication, Department ID Authentication, Access Management System

Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM), SDD Password Lock, SDD Initialize, Mail Box Password Protection, SSD Data Encryption (FIPS140-2 Validated), Verify System at Startup,³ McAfee Embedded Control³

Optional: Data Loss Prevention (Requires uniFLOW)

Network

Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication (v1.0/1.1/1.2/1.3), SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document

Standard: Secure Print, Adobe LiveCycle[®] Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature, User Signatures, Secure Watermark

Environmental Specifications

Operating Environment

Temperature: 50 to 86 °F

Humidity: 20 to 80% RH (Relative Humidity)

Power Requirements

C568iF/
C568iFZ: 110 V-127 V, 60 Hz, 10 A

C478iF/
C478iFZ: 110 V-127 V, 60 Hz, 8.4 A

Plug (Main Unit)

NEMA 5-15P

Power Consumption

Maximum: Approx. 1,500 W

Standby: Approx. 49 W¹⁵

Sleep Mode: Approx. 1.0 W¹⁶

Typical Electricity Consumption (TEC) Rating¹⁷

C568iF/
C568iFZ: 0.67 kWh

C478iF/
C478iFZ: 0.54 kWh

Standards

ENERGY STAR[®] Certified
Rated EPEAT[®] Gold⁵

Consumables

Toner Cartridge

TONER T04 BK/C/M/Y¹⁸

Toner Yield

TONER T04 BK: 33,000 Pages¹⁹

TONER T04

C/M/Y: 27,500 Pages¹⁹

¹ Subscription to a third-party cloud service required. Subject to third-party cloud service providers' Terms and Conditions.

² Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.

³ This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on.

⁴ Requires additional option.

⁵ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.

⁶ Time from device power-on until copy ready (not print reservation).

⁷ Time from exiting Sleep mode to when printing is operational.

⁸ Time from device power-on to when copy jobs can be programmed.

⁹ Includes consumables.

¹⁰ Requires the optional PCL International Font Set-A1.

¹¹ Requires the optional Barcode Printer Kit-D1.

¹² Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix, may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

¹³ Multi-Sheet Feed Detector Supported.

¹⁴ No charge for this solution; however, activation is required.

¹⁵ Reference value (measured one unit).

¹⁶ 1.0 W Sleep mode not available in all circumstances due to certain settings.

¹⁷ Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.

¹⁸ Toner T04L also available for BK and Color (C, M, Y). Yield is BK 11,000 images and Color 9,000 images.

¹⁹ Toner Cartridge yield in accordance with ISO/IEC 19798.

Canon

USA.CANON.COM/SIMPLYADVANCED



As an ENERGY STAR[®] Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Some security features may impact functionality/performance; you may want to test these settings in your environment. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2023 Canon U.S.A., Inc. All rights reserved.

Trellix



To learn about Canon's many awards, visit usa.canon.com/awards.